

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) In a system for providing wireless data communication using a first wireless communications protocol, said system having a host computer adapted to provide management communications with an access point, and ~~[[an]]~~ the access point for conducting wireless data communications with mobile units using said first wireless communications protocol, a method for conducting the management communications between the host computer and the access point comprising:

receiving, by an interface of the access point, the management communications from the host computer over a first connection; and

when a communication failure between the host computer and the access point occurs over the first connection, a radio module of the access point receiving the management communications from a wireless terminal over a second connection, which is different from the first connection, using a second wireless communications protocol to allow management of the access point.

2. (Previously Presented) The method according to claim 1 further comprising at least one of configuring one or more resources of said access point and adjusting one or more parameters of said access point responsive to said received management communications.

3. (Previously Presented) The method according to claim 1 wherein the first wireless communications protocol is an 802.11 Protocol and the second wireless communications protocol is Bluetooth.

4. (Previously Presented) The method according to claim 3, further comprising authenticating said management communications.

5. (Previously Presented) The method according to claim 1 wherein said second wireless communications protocol is Bluetooth.

6. (Previously Presented) The method according to claim 4 further comprising associating said radio module as a slave unit.

7. (Previously Presented) The method according to claim 1, further comprising authenticating said management communications.

8. (Currently Amended) An access point for use in a wireless data communication system, comprising:

- a first interface for conducting data communications with one or more computers adapted to provide management communications with the access point, and for receiving the management communications from the one or more computers over a first connection;

- a first radio module using a first wireless communications protocol for wirelessly transmitting first data messages received from the one or more computers at said first interface to mobile units, and for receiving second data messages from the mobile units and relaying the second data messages to the one or more computers via the first interface;

- at least one processor connected to the first interface and the radio module for controlling the access point; and

- a second radio module operating using a second wireless communications protocol, which is different from the first wireless communications protocol, for receiving the management communications from a wireless terminal over a second connection when a communication failure between the one or more computers and the access point occurs over the first connection.

9. (Previously Presented) The access point as specified in claim 8, wherein said second radio module is arranged to operate as a slave module using a master slave protocol.

10. (Previously Presented) The access point as specified in claim 8, wherein the second radio module is arranged to operate as a slave module using a Bluetooth protocol.

11. (Previously Presented) The access point as specified in claim 8 wherein said processor is further arranged to authenticate communications via said second radio module.

12. (Currently Amended) An apparatus, comprising:
an interface;
a first radio module adapted to provide data communications with mobile units according to a first wireless communications protocol;
a second radio module adapted to communicate with a wireless terminal according to a second wireless communications protocol, which is different from the first wireless communications protocol; and
a processor communicatively coupled to the interface, the first radio module, and the second radio module, the processor adapted to
provide data messages from the interface to the first radio module,
receive, via the interface, management communications from a remote computer
~~via the interface~~ that is adapted to provide the management communications to the apparatus, and
when a communication failure between the remote computer and the apparatus occurs over the interface, to receive the management communications from the wireless terminal via the second radio module.

13. (Previously Presented) The apparatus of claim 12, wherein the processor is adapted to allow data communications through the first radio module and to allow access to management features through the second radio module.

14. (Previously Presented) The apparatus of claim 13, wherein the second radio module operates as a slave unit at least during a portion of the time the access to the management features is allowed.

15. (Previously Presented) The apparatus of claim 12, wherein the processor is further adapted to authenticate communications associated with access of management features.

16. (Previously Presented) The apparatus of claim 12, wherein the first wireless communications protocol is an 802.11 protocol and the second wireless communications protocol is a Bluetooth protocol.

17. (Previously Presented) The apparatus of claim 12, wherein the processor is further adapted to allow monitoring of the data communications.

18. (Previously Presented) The method according to claim 1, wherein receiving the management communications comprises receiving one or more communications selected from a group of communications that includes updated system information, modified system programming, information concerning association with the mobile units, data for use by access points, and software for use by access points.

19. (Previously Presented) The method according to claim 1, further comprising monitoring the wireless data communication using the second wireless communications protocol.

Application No.: 09/911,670

Reply to Final Office Action mailed on 12/11/2007

20. (Previously Presented) The access point as specified in claim 8, wherein the at least one processor further allows monitoring the data communications using the second wireless communications protocol.